QVNU2.E355391 Protectors, Supplementary - Component

Page Bottom

Protectors, Supplementary - Component

See General Information for Protectors, Supplementary - Component

NOARK ELECTRIC USA INC

E355391

2188 Pomona Blvd Pomona, CA 91768 USA

Supplementary protector, Cat No. B1E.

Cat. No.	Туре	UG	FW	Max V	Max Amps	тс	OL	sc	Operation
B1E, 1 pole	oc	Α	2	120Vac	1 - 63 A	3	1	10 kA, U1	Trip-free
	ос	Α	2	240Vac	1 - 63 A	3	1	10 kA, U1	Trip-free
	ос	Α	2	277Vac	1 - 63 A	3	1	5 kA, U1	Trip-free
	ос	Α	2	60Vdc	1 - 63 A	3	0	10 kA, U1	Trip-free
B1E, 2, 3 and 4 pole	ос	Α	2	125Vdc	1 - 63 A	3	0	10 kA, U1	Trip-free
	ос	А	2	240Vac	1-63 A	3	1	10 kA, U1	Trip-free
	ос	Α	2	480Vac	1 - 63 A	3	1	5 kA, U1	Trip-free
B1E, followed by 1P, 2P, 3P or 4P, followed by 63, 80, 100 or 125.	ос	А	0	120/240, 208, 240, 277	63 - 125	2	0	5kA, U1	Trip-free
	ос	Α	0	480	63- 125	2	0	5kA, U1	Trip-free
	ос	Α	0	60, 110 Vdc	63- 125	1	0	10KA, U1	Trip-free
	ос	Α	0	110, 220 Vdc	63- 125	1	0	10KA, U1	Trip-free
Ex9BPH, followed by 1P, 2P, 3P or 4P, followed by C or K, followed by xx (10A to 40A)	ОС	Α	0	600 Vdc	10-40	3	0	10KA, U1	Trip-free
Ex9BPN, followed by 1P, 2P, 3P or 4P, followed by C or K, followed by xx (10A to 40A)	OC	Α	0	600 Vdc	10-40	3	0	6KA, U1	Trip-free

Accessory auxiliary switch, Cat Nos. AX31, f/b 11, f/b U.

Accessory undervoltage trip, Cat Nos. UVT31, may be f/b 01 or 10, f/b U, f/b A or B.

Accessory shunt trip, Cat Nos. SHT31, may be f/b 11, f/b U, f/b A, B or C.

Marking: Company name or trademark



Last Updated on 2016-02-26

<u>Questions?</u> <u>Print this page</u> <u>Terms of Use</u> <u>Page Top</u>

♦ 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".